

# Preformed Galvanized Aircraft Cable

Not For Aircraft Use.



| Diameter In Inches | Approx. Weight 100 Ft. In LBS | Min. Strength In LBS |
|--------------------|-------------------------------|----------------------|
|                    |                               |                      |
| 3/64               | 0.36                          | 270                  |
| 3/64               | 0.36                          | 270                  |
| 1/16               | 0.75                          | 480                  |
| 1/16               | 0.75                          | 480                  |
| 3/32               | 1.6                           | 920                  |
| 3/32               | 1.6                           | 920                  |
| 1/8                | 2.8                           | 1700                 |
| 5/32               | 4.3                           | 2600                 |
| 3/16               | 6.2                           | 3700                 |
| 7/32               | 8.3                           | 4800                 |
| 1/4                | 10.6                          | 6100                 |
| 5/16               | 16.7                          | 9200                 |
| 3/8                | 23.6                          | 13300                |



| Diameter In Inches | Approx. Weight 100 Ft. In LBS | Min. Strength In LBS |
|--------------------|-------------------------------|----------------------|
|                    |                               |                      |
| 1/16               | 0.75                          | 480                  |
| 3/32               | 1.7                           | 1000                 |
| 3/32               | 1.7                           | 1000                 |
| 1/8                | 2.9                           | 2000                 |
| 1/8                | 2.9                           | 2000                 |
| 5/32               | 4.5                           | 2800                 |
| 5/32               | 4.5                           | 2800                 |
| 3/16               | 6.5                           | 4.2                  |
| 3/16               | 6.5                           | 4.2                  |
| 7/32               | 8.6                           | 5600                 |
| 7/32               | 8.6                           | 5600                 |
| 1/4                | 11                            | 7000                 |
| 1/4                | 11                            | 7000                 |
| 9/32               | 13.9                          | 8000                 |
| 9/32               | 13.9                          | 8000                 |
| 5/16               | 17.3                          | 9800                 |
| 5/16               | 17.3                          | 9800                 |
| 3/8                | 24.3                          | 14400                |
| 3/8                | 24.3                          | 14400                |