



Stainless Steel Cable Strand & Ropes

Non-flexible Type 302/304/316



SSAC 1X19		
Diameter In Inches	Approx. Weight 100 Ft. In LBS	Min. Strength In LBS
3/64	0.55	375
3/64	0.55	375
1/16	0.85	500
1/16	0.85	500
5/64	1.4	800
5/64	1.4	800
3/32	2	1200
3/32	2	1200
7/64	2.7	1600
7/64	2.7	1600
1/8	3.5	2100
1/8	3.5	2100
5/32	5.5	3300
5/32	5.5	3300
3/16	7.7	4700
3/16	7.7	4700
7/32	10.2	6300
7/32	10.2	6300
1/4	13.5	8200
1/4	13.5	8200
9/32	17	10300
9/32	17	10300
5/16	21	12500
5/16	21	12500
3/8	29.4	17500
3/8	29.4	17500
7/16	41	22500
1/2	52.1	30000
9/16	67	36200
5/8	85.5	47000

SSAC 7X7		
Diameter In Inches	Approx. Weight 100 Ft. In LBS	Min. Strength In LBS
1/32	0.2	115
3/64	0.42	270
3/64	0.42	270
1/16	0.75	480
1/16	0.75	480
5/64	1.1	650
3/32	1.6	920
3/32	1.6	920
7/64	2.2	1260
1/8	2.8	1700
5/32	4.3	2400
3/16	6.2	3700
7/32	8.3	4800
1/4	10.6	6100
9/32	13.4	7400
5/16	16.7	9000
3/8	23.6	12000
7/16	34.2	15600
1/2	44	21300
9/16	55	26600
5/8	68	32500
3/4	97	46000

SSAC 7X19		
Diameter In Inches	Approx. Weight 100 Ft. In LBS	Min. Strength In LBS
3/64	0.42	270
1/16	0.75	480
1/16	0.75	480
3/32	1.7	920
3/32	1.7	920
7/64	2.3	1260
1/8	2.9	1760
1/8	2.9	1760
5/32	4.5	2400
5/32	4.5	2400
3/16	6.5	3700
3/16	6.5	3700
7/32	8.6	5000
7/32	8.6	5000
1/4	11	6400
1/4	11	6400
9/32	13.9	7800
9/32	13.9	7800
5/16	17.3	9000
5/16	17.3	9000
3/8	24.3	12000
3/8	24.3	12000