



## POLYESTER ROUNDSLING

**ASC** polyester slings are made in several capacities. vertical. These Roundslings conform to ASME B30.9 Chapter six. They have a double Polyester outer cover made from the same color. The core yarn is also polyester.

These slings are color coded to depict a certain sling capacity. However, be aware that the color code of Roundslings is NOT governed by ASME B30.9. Never select a sling by it's color. Always read the tag information.



## SPECIFICATION AND DIMENSIONS (inches and lbs.)

		Work Load in Lbs.			width		Base
Part No.	Color	Vertical	Choker	Basket	at load	lbs./ft	length/ft
ER1	Purple	2600	2100	5200	1-1/8"	0.2	3
ER2	Green	5300	4200	10600	1-1/2"	0.3	3
ER3	Yellow	8400	6700	16800	1-7/8"	0.5	3
ER4	Tan	10600	8500	21200	2-1/8"	0.6	3
ER5	Red	13200	10600	26400	2-1/4"	0.8	3
ER6	White	16800	13400	33600	2-1/2"	0.9	3
ER7	Blue	21200	17000	42400	3"	1.3	3
ER9	Gray	31000	24800	62000	3-3/4"	1.7	3
ER11	Brown	53000	42400	106000	4-5/8"	2.8	3

Can fail if damaged, misused or overloaded. Inspect before use. Use only if trained. Observe rated capacity. Protect sling from contact with edges. Avoid exposure to acid, alkali, sunlight and temperature over 180°F. DEATH or INJURY can occur from improper use or maintenance.

